

BLUE HOSE

MANUFACTURERS SPECIFICATIONS

- **COLOUR** – Light blue with blue spiral
- **TEMPERATURE RANGE** – 10°C to 50°C

FEATURES

- Platicised PVC hose with spiral reinforcement of anti-shock rigid PVC
- Smooth bore
- Lightly corrugated external surface
- Very light and flexible compared to rubber hose and more durable
- Cold resistant
- Not recommended to prolonged UV exposure

APPLICATIONS

- Suction and discharge of liquids, abrasive powders, fumes, vapours and shavings
- Recommended for diesel fuels, liquid petroleum products, lubricating oils, mineral oils, light oils and transformer oils.



OUR CODE	DESCRIPTION	SIZE "	WALL THICKNESS mm	WORKING PRESSURE		BENDING RADIUS mm	VACUUM negative kpa
				kg/cm2	psi		
BH 020-30M	20mm x 30m	3/4"	2.2	5	70	40	80
BH 025-30M	25mm x 30m	1"	2.2	5	70	40	80
BH 032-30M	32mm x 30m	1.1/4"	2.4	5	70	40	70
BH 040-30M	40mm x 30m	1.1/2"	2.6	5	70	60	70
BH 050-30M	50mm x 30m	2"	3.0	5	70	90	70
BH 076-30M	76mm x 30m	3"	3.4	4	57	110	50
BH 100-30M	100mm x 30m	4"	4.3	4	57	160	40